

NGBS GREEN CERTIFIED TM

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

KOPPERS NATUREWOOD CA - COPPER AZOLE CA-C TREATED WOOD

MANUFACTURED BY

KOPPERS PERFORMANCE CHEMICALS

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC-700 NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.

Michael Luzier - Presidentia CEO

April 26, 2013

July 31, 2024 Expiration Data **CERTIFICATE #000224**

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer



NGBS Green Certificate #NGBSGCP-000224

Products: Koppers NatureWood CA - Copper Azole CA-C Treated Wood

Manufacturer: Koppers Performance Chemicals

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2015 NATIONAL GREEN BUILDING STANDARD					
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points		
2015 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	5	Retaining walls built with this product must be an integal part of the installed landscape plan designed to limit long term erosion.		
2015 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.		

2020 NATIONAL GREEN BUILDING STANDARD					
PRACTICE #	PRACTICE DESCRIPTION	POTENTI AL POINTS AVAILA BLE	Additional Conditions of Use to Award Points		
2020 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integal part of the installed landscape plan designed to limit long term erosion.		
2020 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.		